



## PROFESSIONAL ACHIEVER™ POWER DIRECT VENT

THE PERFECT CHOICE FOR TIGHT CONSTRUCTION  
OR WHEN INDOOR AIR QUALITY IS A CONCERN FOR  
LIMITED SPACES



### Efficiency:

- .67 EF
- Energy Star® rated

### Performance

- FHR: Up to 93 gallons for natural and LP gas
- Recovery: 38.4 to 40.4 GPH at a 90°F rise, depending on model

### Self-Diagnostic System

- Electronic gas control for improved monitoring and service

### Low Emissions

- Eco-friendly burner, low NOx design

### Features

- Two pipe system: one pipe pulls in outside air for combustion and the other exhausts combustion gases
- 120 VAC powered blower
- New whisper quiet blower

### Flammable Vapor

- Protective control system that disables the heater in the presence of flammable vapor accumulation



RELY ON RUUD.™

# PROFESSIONAL ACHIEVER™ POWER DIRECT VENT



## Flexible Venting Options

- Long venting lengths up to 100 feet
- PVC, ABS, or CPVC vent pipe options
- Vertical or horizontal termination
- Concentric vent kit available

## Longer Life

- Premium grade anode rod provides long-lasting tank protection

## High Altitude Compliant

- Models are certified for applications up to 10,200 feet above sea level

## Plus...

- Enhanced flow brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant
- Durable silicon nitride igniter (HSI)
- EverKleen™ patented system fights sediment build-up
- Standard replacement parts

## Warranty

- 6-Year limited for the tank
- 6-Year limited for the parts



DESCRIPTION			FEATURES						ENERGY FACTOR	
TYPE	GAL. CAP.	MODEL NUMBER	GAS INPUT IN THOUS. BTU/H		RECOVERY IN G.P.H. 90° RISE		FIRST HOUR DELIVERY DEL. GPH		NAT	LP
			NAT	LP	NAT	LP	NAT	LP		
Tall	40	PROG40-40N RU67 PDV	40	-	40.4	-	73	-	0.67	-
Tall	40	PROG40-38P RU67 PDV	-	38	-	38.4	-	73	-	0.67
Tall	50	PROG50-40N RU67 PDV	40	-	40.4	-	93	-	0.67	-
Tall	50	PROG50-40P RU67 PDV	-	40	-	40.4	-	93	-	0.67