# POINT-OF-USF FLECTRIC



#### **Point-of-Use Tank Benefits**

Well-suited for a wide variety of applications, point-of-use water heaters are small enough for installations in limited spaces...under counters, mop sinks, cabinets, or any remote area where modest quantities of hot water are required. They are ideally suited for applications in retail stores, public restrooms, office washrooms, kitchen and mop or bar sinks.

#### **Point-of-Use Tank Features**

- 2-1/2, 6, 10, 15, 19.9 and 30-Gallon capacities
- 1440 Watts through 6,000 Watts
- 120, 208, 240, 277 and 480 Voltages
- Single phase only
- Premium grade anode rod provides advanced technology and equalizes aggressive water action

## Long Life Tank Design

- Proprietary steel formulation with a unique coat of high temperature porcelain enamel
- Maximizes corrosion resistance resulting in a superior tank design

# **Long Life Heating Elements**

- Patented resistor elements are designed with a specially treated, double layer of magnesium oxide and copper to resist corrosion
- Rigid polyurethane foam insulation provides superior insulating qualities resulting in reduced operating costs
- A surface mounted thermostat automatically cycles on and off to maintain the water temperature at a desired preset level
- 170°F maximum temperature setting (except 2-1/2 gallon model)
- Temperature limiting control
- Temperature and pressure relief valve

### **Optional Wall Mounting Kit**

- Provides an easy way to mount the unit off the floor, out of the way for more usable floor space in a small area
- Kit is designed to be used on walls with 16" stud centers
- All necessary parts are included in this easy to install kit
- 2-1/2 Gallon model comes standard with the kit

#### Warranty

• 3-Year limited tank warranty, upgradable to 5 years

#### Point-of-Use Tank Models

| DESCRIPTION  |                 |               |               | DIMENSIONS (INCHES) |        |                      |
|--------------|-----------------|---------------|---------------|---------------------|--------|----------------------|
| GAL.<br>CAP. | MODEL<br>NUMBER | MIN.<br>WATTS | MAX.<br>WATTS | HEIGHT              | WIDTH  | SHIP<br>WT.<br>(LB.) |
| 2.5          | EGSP2           | 1,440         | 1,500         | 14                  | 9-3/4  | 18                   |
| 6            | EGSP6           | 1,500         | 6,000         | 15-1/8              | 15-3/4 | 41                   |
| 10           | EGSP10          | 1,500         | 6,000         | 22-7/8              | 15-3/4 | 53                   |
| 15           | EGSP15          | 1,500         | 6,000         | 24-1/4              | 17-3/4 | 65                   |
| 19.9         | EGSP20          | 1,500         | 6,000         | 25-1/8              | 19-3/4 | 76                   |
| 30           | EGSP30          | 1,500         | 6,000         | 30                  | 21-3/4 | 115                  |







