

Packaged

AIR CONDITIO[°]NERS



The new degree of comfort.™

SSNM Series



R-410A
50Hz

14-gauge G-90 sheet metal base rails allow for easier maneuverability during installation

Pre-paint system rated at 1000 hour salt spray per ASTM B117.

Full-louver coil protection

Easy-to-access control box and internal components

High and low refrigerant pressure gauge ports for easy pressure measurement

Removable, sloped drain pan

Foil-faced insulation to the cabinet

Closed-cell insulation on the base of the unit

TECHNICAL DATA

SSNM		SSNM-A024TK	SSNM-A036TK	SSNM-A042NK	SSNM-A048NK	SSNM-A048TK	SSNM-A060NK	SSNM-A072NK
Rated Cooling Capacity @AHRI	Btu/hr	21000	31000	36000	40000	42000	52000	63500
EER @AHRI	Btu/W-hr	11.3	11.3	11.1	11.3	11.3	11.3	10.65
Rated Air Flow	CFM	665	1000	1165	1290	1290	1585	2200
Unit Sizes	L (mm)	1499	1499	1499	1499	1499	1499	1499
	W (mm)	838	838	838	838	838	838	838
	H (mm)	740	740	740	943	943	943	943
Weight	kg	148	159	166	186	186	212	217
Refrigerant	R410A							

AHRI Condition: 80°F/67°F On-coil, 95°F ambient

Before proceeding with installation, refer to the installation instructions packaged with each model, as well as complying with all Federal, State, Provincial and local codes, regulation and practices.

RHEEM MANUFACTURING MEA FZE

Dubai Airport Freezone (DAFZA), UAE

"In keeping with its policy of continuous progress and product improvement, Rheem reserves the rights to make changes without notice."