

Packaged

# AIR CONDITIONERS



The new degree of comfort.™

## SSPM Series



R-410A  
60Hz

14-gauge G-90 sheet metal base rails allow for easier maneuverability during installation

Full-louver coil protection

Easy-to-access control box and internal components

Number and color-coded wiring

High and low refrigerant pressure gauge ports for easy pressure measurement

Removable, sloped drain pan

Foil-faced insulation to the cabinet

Closed-cell insulation on the base of the unit

Scroll compressor for reliable, efficient and quiet operation

# TECHNICAL DATA

SSPM		SSPM-A024JK	SSPM-A030JK	SSPM-B036JK	SSPM-B043JK	SSPM-A048JK	SSPM-B060JK
Rated Cooling Capacity @AHRI	Btu/hr	23500	28500	34000	40500	46500	58500
Rated Cooling Capacity @T3	Btu/hr	22000	25500	30000	36000	41000	50800
EER @AHRI	Btu/W-hr	11.6	11.8	11.6	11.5	11.5	11.5
EER @T3	Btu/W-hr	8.3	8.3	8.3	8.3	8.3	8.3
Rated Air Flow	CFM	800	1000	1200	1400	1600	1900
Unit Sizes	L (mm)	1499	1499	1499	1499	1499	1499
	W (mm)	838	838	838	838	838	838
	H (mm)	740	740	740	740	943	943
Weight	kg	138	139	140	151	158	165
Refrigerant		R410A					

**AHRI Condition: 80°F/67°F On-coil, 95°F ambient**

**T3 Condition: 29°C/19°C On-coil, 46°C ambient**

Before proceeding with installation, refer to the installation instructions packaged with each model, as well as complying with all Federal, State, Provincial and local codes, regulation and practices.

**RHEEM MANUFACTURING MEA FZE**

Dubai Airport Freezone (DAFZA), UAE

"In keeping with its policy of continuous progress and product improvement, Rheem reserves the rights to make changes without notice."