

HEAVY DUTY GAS

Xtreme: High-input, fast recovery gas water heaters that comply with low NOx emissions

These 90-gallon models range from 500,000-715,000 Btu/h and deliver up to 756 gallons per hour at a 100 degree F rise.



Xtreme™ Benefits

Xtreme is an advanced line of fast recovery commercial gas water heaters. These products can deliver up to 756 gallons per hour at 100 degree F rise. The small jacket diameter makes it a popular choice for retro fits and it is a versatile choice for new construction.

Xtreme Space Saver Design

Xtreme maximizes installation adaptability by offering models with front and rear inlet/outlet water connections. Short heights and small jacket diameters result in greater installation flexibility.

Xtreme Features

- 80% Thermal efficiency
- 500,000-715,000 Btu/h
- 90-Gallon capacity
- 180° F Maximum temperature setting



- Exclusive System Sentinel LED diagnostic system with glowing LED lights verifies system operation sequence by sequence
 - Patented multi-flue design with proprietary steel formulation and two coats of porcelain enamel for a superior heat exchanger design
 - Low profile automatic flue damper
 - Five premix burners mounted into a metal face plate and sealed with a Viton gasket. Patented “quick release” manifold for easier service
 - Direct spark-to-pilot ignition system
 - Precision round premix burners formed from chromium stainless steel
 - Full-port, full-flow brass drain valve
 - Patented magnesium anode rods for long tank life
 - Standard natural and LP models are certified up to 2,000 feet above sea level; 8,000 feet for high altitude models
 - Natural and LP models
- Warranty**
- 3-Year limited tank warranty, upgradable to 5 years

Xtreme Models

DESCRIPTION				DIMENSIONS (INCHES)			
GAL. CAP.	MODEL NUMBER	INPUT (BTU/H) NAT. & LP	THERMAL EFF.	HEIGHT	WIDTH	VENT	SHIP WT. (LB.)
90	GX90-550(A)	550,000 (NAT)	80%	68	30	10	905
	GX90-640(A)	640,000 (NAT)	80%	68	30	10	905
	GX90-715(A)	715,000 (NAT)	80%	68	30	10	905
	GX90-500(A)	500,000 (LP)	80%	68	30	10	905
	GX90-600(A)	600,000 (LP)	80%	68	30	10	905
	GX90-680(A)	680,000 (LP)	80%	68	30	10	905

*Weights listed are for non-ASME. Add 40 lbs. for ASME models.
(A) indicates available ASME model.

Download spec sheet from Rheem.com or ask for form RR102C-15