

MEDIUM DUTY GAS

Power Vent: Designed to deliver medium quantities of hot water and provide up to 95 foot vent runs

These 75-gallon models are available in 75,000 Btu/h with a maximum temperature setting of 160 degrees F.



Power Vent Benefits

They vent up to 95 feet and are easily installed in large residences, small restaurants, apartments up to six units and small office buildings.

Power Vent Features

- 80% Thermal efficiency
- 75,100 Btu/h
- 75-Gallon capacity
- 160° F Maximum temperature setting
- Superior tank design features proprietary steel formulation with a unique coat of high temperature porcelain enamel to maximize corrosion resistance
- FVIR compliant, maintenance free with no filters to clean
- Flammable vapor detection sensor disables the heater in the presence of flammable vapor accumulation
- Integrated self-diagnostic system



Easier, Less Costly Venting

- Installs with PVC, ABS, or CPVC vent options with vertical or horizontal termination
- Side connections available for ease of installation and flexibility
- Maximum vent length is 95 equivalent feet using 4" PVC
- Vents up to 35 equivalent feet using 3" PVC pipe
- Integral automatic powered blower assists quietly bringing in combustion air and discharging combustion gases
- Environmentally friendly burner is 40ng/J NOx compliant
- Patented magnesium anode rod design with resistor protects the tank from corrosion
- Hot surface ignition (HSI) for less fuel consumption versus a standing pilot
- Self-cleaning
- Full-port, full-flow brass drain valve
- CSA/ASME rated temperature and pressure relief valve
- Certified up to 7,700 feet above sea level
- Natural and LP models

Warranty

- 3-Year limited tank warranty, upgradable to 5 years
- 1-Year limited parts warranty

Download spec sheet from Rheem.com or ask for form RR102C-4

Power Vent Models

DESCRIPTION				DIMENSIONS (INCHES)			
GAL. CAP.	MODEL NUMBER	INPUT (BTU/H) NAT. & LP	THERMAL EFF.	HEIGHT	WIDTH	VENT	SHIP WT. (LB.)
75	GPV75-76FV-2	75,100	80%	60-1/8	26-1/4	3, 4	330
	GPV75-76PFV-2	75,100	80%	60-1/8	26-1/4	3, 4	330

