

FURY



The Fury® electric water heater line is engineered for longer life – resisted heating elements and premium grade anode rod

Efficiency:

- .85 - .95 EF
- Isolated tank design reduces conductive heat loss
- High efficiency stainless steel heating element for added protection to prolong anode rod and tank life

Performance:

- FHR: 42 - 99 gallons, based on gallon capacity
- Recovery rate is 21 gallons at a 90° F
- High Efficiency Models Feature High performance and lower operating cost
- Exclusive Rheemglas tank lining resists corrosion
- ASME rated temperature and pressure relief valve
- R-Foam insulation for superior heat retention
- Maximum tank working pressure of 150 PSI (10 BARS)
- Factory tested @ 300 PSI
- Anode rod equalizes aggressive water action and prolongs the life of the water heater
- Electric Junction box located above heating elements for easy installation
- Over-temperature protector cuts off power in excess temperature situations
- Thermostat keeps water at desired temperature
- Available in 208V, 220V, 230V, 240V, 380V, 400V, 415V and 480V
- Available in Single Phase and 3 Phase
- Available in 2, 2.5, 3, 4.5, 5, 5.5 and 6 Kw with different options of Simultaneous and Non-Simultaneous heating elements



FURY

Plus...

- EverKleen™ self-cleaning device fights harmful sediment build-up with a high-velocity spiraling water stream helps operating efficiency by saving energy, money and improving tank life
- Brass drain valve
- Temperature and pressure relief valve
- Meets LEED requirements
- Stainless Steel or Incoloy Heating elements available

Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts



DESCRIPTION			FEATURES		ROUGHING IN DIMENSIONS (SHOWN IN INCHES)				ENERGY INFO
TYPE	GAL. CAP.	MODEL NUMBER	FIRST HOUR RATING G.P.H.	RECOVERY IN G.P.H. 90°F RISE	TANK HEIGHT	HEIGHT TO WATER CONN.	DIAMETER	APPROX. SHIP. WT (LBS)	ENERGY FACTOR
TALL	30	82V30-2	48	21	45-3/4	45-3/4	17-3/4	80	0.93
	40	83VR40-2†	56	21	46-3/4	46-3/4	22-1/4	104	0.95
	40	82V40-2	53	21	46-1/2	46-1/2	19-3/4	95	0.92
	40	82VH40-2	57	21	59-1/4	59-1/4	17-3/4	96	0.92
	50	83VR52-2†	67	21	57	57	22-1/4	123	0.95
	50	82V52-2	67	21	57	57	19	107	0.91
	65	83VR66-2†	71	21	58-3/4	58-3/4	23	160	0.92
	65	82V66-2	71	21	58-1/2	58-1/2	21	150	0.89
	80	83VR80-2†	88	21	59	59	24-1/2	181	0.92
	80	82V80-2	88	21	59	59	23	177	0.86
MED	120	82V120-2	99	21	62-1/2	62-1/2	28-1/4	324	0.85
	30	82MV30-2	44	21	36	36	19-3/4	80	0.93
	50	83MVR52-2†	62	21	46	46	24-1/4	128	0.93
SHORT	50	82MV52-2	62	21	46	46	21-3/4	117	0.9
	20	82SV20-2	-	21	31-1/2	31-1/2	17	62	N/A
	30	81SVB30-2*	42	21	30	30	19-3/4	90	0.93
	30	82SV30-2	42	21	30	30	22-1/4	83	0.93
	38	82SV40-2	45	21	31-1/2	31-1/2	23	108	0.92
	38	82SVB40-2*	45	21	31-1/2	31-1/2	23	108	0.93
T	47	82SV50-2	55	21	32	32	26-1/4	149	0.91

* Water heater dimensions prior to installing insulation blanket that is included with water heater

81SVB30-2 - The insulation blanket adds 1-1/2 inches to tank height and 3 inches to tank diameter.

82SVB40-2 - The insulation blanket adds 1 inch to tank height and 2 inches to tank diameter

